

STANDARD ARRIVAL
ROUTES INSTRUMENT
(STAR)

SANTIAGO
CIBAO INTL
RNAV (GNSS) RWY29

Designator	Identification Significant Points	Constraints	MAG (True) Track	Dist NM	MNM IFR Cruising Level	Remarks
BEPAL 1R	BEPAL ONE ROMEO					
	Δ BEPAL	A10000+;K250-	028(016.7)	20.8	9000	
	Δ ST521	A10000+;K250-;R	100(088.6)	16.7	5000	
	Δ ST522	A7000+;K220-	100(088.7)	11.7	4000	
	Δ ST525	A5000+;K210-;R	114(103.0)	7.0	3000	
	Δ LEPUR	A4000+;K210-	114(103.1)	12.4	3000	
BESAS 1R	BESAS ONE ROMEO					
	Δ BESAS	A9000+;K250-	184(173.4)	45.4	3000	
	Δ ST528	A6000+;K220-;R	229(218.2)	11.8	4000	
PETRI 1R	PETRI ONE ROMEO					
	Δ PETRI	A9000+;K250-	293(281.8)	31.1	5000	
	Δ ST527	A5000+;K220-	293(281.8)	8.0	4000	
RETAK 1R	RETAK ONE ROMEO					
	Δ RETAK	A9000+;K250-	144(132.5)	54.5	5000	
	Δ ST523	A8000+;K250-	144(132.7)	18.4	3000	
	Δ ST525	A5000+;K210-;L	114 (103.0)	7.0	3000	
	Δ LEPUR	A4000+;K210-	114 (103.1)	12.4	3000	
	Δ KERDA	A4000+;K210-				
RIBES 1R	RIBES ONE ROMEO					
	Δ RIBES	A9000+;K250-	289(278.3)	19.2	3000	
	Δ ST526	A5000+;K210-	289(278.2)	8.0	3000	
SEKAR 1R	SEKAR ONE ROMEO					
	Δ SEKAR	A9000+;K250-	198(186.8)	46.6	5000	
	Δ ST524	A8000+;K250-;L	164(152.8)	18.4	5000	
	Δ ST525	A5000+;K210-	114(103.0)	7.0	3000	
	Δ LEPUR	A4000+;K210-	114(103.1)	12.4	3000	
	Δ KERDA	A4000+;K210-				
DME/DME not authorized.						